


AUGER Glandpacking

TYPE : AP 4030



Gland packing braided by PTFE graphite yarn impregnated with a special lubricant.

- Used for pumps, mixers and valves.
- Suitable for acids and for bases.
- Water and steam till 280 °C
- Very chemical resistant, very flexible, does not lose volume.
- Good thermal conductivity.

| Dimensions mm | Packaging | m/kg | g/m |
|---------------|-----------|-------|------|
| 4 x 4 mm | 1 kg | 41.67 | 24 |
| 6 x 6 mm | 1 kg | 16.52 | 59 |
| 8 x 8 mm | 1 kg | 9.42 | 106 |
| 10 x 10 mm | 2 kg | 6.07 | 165 |
| 12 x 12 mm | 2 kg | 4.21 | 238 |
| 14 x 14 mm | 4 kg | 3.09 | 323 |
| 16 x 16 mm | 4 kg | 2.37 | 422 |
| 18 x 18 mm | 4 kg | 1.87 | 535 |
| 20 x 20 mm | 5 kg | 1.67 | 660 |
| 22 x 22 mm | 5 kg | 1.25 | 700 |
| 24 x 24 mm | 5 kg | 1.06 | 950 |
| 25 x 25 mm | 5 kg | 0.87 | 1031 |

SPECIFICATIONS

-Pmax pumps : 30 bar
 -Pmax valves : 200 bar
 -PH : 0 - 14
 -V : 20 m/s
 -T° : -100°C - +280°C

APPLICATIONS

-Chemical industrie
 -Power plants
 -Oil refining
 -Pharmaceutical industries
 -Food industries

REMARKS

-Other dimensions on request.

AUGER_{N.V.}

Kemelbeekstraat 30—2460 Tienen—Belgium
 T +32 (0)14 86 03 55 E info@auger.be W www.auger.be