

AUGER Glandpacking

TYPE : AP 4030 G



Gland packing braided by PTFE graphite

Yarn GORE-TEX

- Used for pumps, mixers and valves.
- Suitable for acids and for bases.
- Water and steam till 280°C
- Very chemical resistant, very flexible, does not lose volume.
- Good thermal conductivity.

Dimensions mm	Packaging	m/kg	g/m
4 x 4 mm	1 kg	41.67	24
6 x 6 mm	1 kg	16.52	59
8 x 8 mm	1 kg	9.42	106
10 x 10 mm	2 kg	6.07	165
12 x 12 mm	2 kg	4.21	238
14 x 14 mm	4 kg	3.09	323
16 x 16 mm	4 kg	2.37	422
18 x 18 mm	4 kg	1.87	535
20 x 20 mm	5 kg	1.67	660
22 x 22 mm	5 kg	1.25	700
24 x 24 mm	5 kg	1.06	950
25 x 25 mm	5 kg	0.87	1031

SPECIFICATIONS

-Pmax pumps : 30 bar
 -Pmax valves : 200 bar
 -PH : 0 - 14
 -V : 20 m/s
 -T° : -100°C - +280°C

APPLICATIONS

-Chemical industrie
 -Power plants
 -Oil reining
 -Pharmaceutical industries
 -Food industries

REMARKS

-other dimensions on request.



Kemelbeekstraat 30—2460 Tienen—Belgium
 T +32 (0)14 86 03 55 E info@auger.be W www.auger.be