


AUGER Glandpacking

TYPE : AP 5050P



Gland packing braided by PTFE yarn, reinforced by aramid yarn, impregnated.

- Used for pumps and valves.
- Suitable for acids and for bases.
- Suitable for water and steam till 280 °C.
- Very chemical resistant, very flexibel, does not lose volume.
- Good thermal conductivity.

Dimensions mm	Packaging	m/kg	g/m
4 x 4 mm	1 kg	41.67	24
6 x 6 mm	1 kg	18.52	54
8 x 8 mm	1 kg	10.42	96
10 x 10 mm	2 kg	6.67	150
12 x 12 mm	2 kg	4.63	216
14 x 14 mm	4 kg	3.40	294
16 x 16 mm	4 kg	2.60	384
18 x 18 mm	4 kg	2.06	486
20 x 20 mm	5 kg	1.67	600
22 x 22 mm	5 kg	1.38	726
24 x 24 mm	5 kg	1.16	864
25 x 25 mm	5 kg	1.07	937.5

SPECIFICATIONS

-Pmax pumps : 30 bar
 -Pmax valves : 250 bar
 -PH : 1 - 13
 -V : 25 m/s
 -T° : -150°C - +280°C

APPLICATIONS

-Chemical industries
 -Power plants
 -Oil refining
 -Pharmaceutical industries
 -Piston pumps
 -Sand containing media.

REMARKS

-other dimensions on request.

AUGER_{N.V.}

Kemelbeekstraat 30—2460 Tienen—Belgium
 T +32 (0)14 86 03 55 E info@auger.be W www.auger.be