

▶ AUGER SEAL TYPE AR2

▼ WE SEAL PUMPS!



Diameter d1	d3	d7	l3	l4	l1
10	17,50	18,10	15,20	5,50	20,70
12	20,00	20,60	18,20	5,50	23,70
14	23,00	23,10	22,20	6,00	28,20
15	24,00	26,90	22,20	7,00	29,20
16	26,00	26,90	23,20	7,00	30,20
17	27,00	26,90	23,20	7,00	30,20
18	29,00	30,90	24,20	8,00	32,20
19	30,00	30,90	25,20	8,00	33,20
20	30,00	30,90	25,20	8,00	33,20
22	34,00	35,40	25,20	8,00	33,20
24	35,00	35,40	27,20	8,00	35,20
25	37,00	38,20	27,20	8,50	35,70
26	38,00	38,20	27,20	8,50	35,70
28	42,00	43,30	29,20	9,00	38,20
30	43,00	43,30	30,20	9,00	39,20
32	45,00	43,30	30,20	9,00	39,20
33	48,00	53,50	39,20	11,50	50,70
35	50,00	53,50	39,20	11,50	50,70
38	54,00	60,50	39,20	11,50	50,70
40	56,00	60,50	39,20	11,50	50,70
42	59,00	60,50	39,20	11,50	50,70
43	60,00	60,50	39,20	11,50	50,70
45	64,00	65,50	41,20	11,50	52,70
48	68,00	65,50	41,20	11,50	52,70
50	69,00	72,50	45,20	11,50	56,70
55	74,00	72,50	47,20	11,50	58,70
60	80,00	79,30	49,20	11,50	60,70
65	87,00	84,50	51,20	11,50	62,70
70	92,00	89,50	51,20	11,50	62,70
75	97,00	94,50	57,20	11,50	68,70
80	102,00	99,50	59,20	11,50	70,70
85	110,00	105,50	59,20	13,50	72,70
90	117,00	111,50	62,20	13,50	75,70
95	122,00	116,50	62,20	13,50	75,70
100	127,00	119,50	75,20	13,50	88,70

SPECIFICATIONS

- Pmax: 12 bar
- T°C: -30 ~ 200 °C
- Single directional
- Left or right spring
- Unbalanced

APPLICATIONS

- Centrifugal pumps
- Submersible pumps
- Water pumps

MATERIALS

- Faces rotary: st/st, Q, Carbon TC
- Metal parts: st/st 304 & 316
- O-rings: Viton, EPDM, a.o

REMARKS

- Q and TC is shrunk in
- Standard with right spring

AUGER_{N.V.}

Kemelbeekstraat 30 - 2460 TIELEN - Belgium

T +32 (0)14 86 03 55 E info@auger.be W www.auger.be